

WARNING : PLEASE PRINT THE DOCUMENT
CHOOSING ACTUAL SIZE. DO NOT SELECT
FIT TO PAGE IN YOUR PRINTER SET UP.



MEASURE UP TO THIS LINE ^

cm

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

WRIST-SIZING INSTRUCTIONS FOR STAINLESS STEEL BRACELETS



STEP 1

Print this file and cut out the ruler
(on the left).



STEP 2

Place the watch dial on top of your wrist
and wrap the ruler around your wrist.



STEP 3

Once the ruler is fully wrapped around
your wrist, write down the size that
is aligned with the red line (below the
watch's dial). Use this number to select
the closest option from the "Bracelet
Size" menu.



STEP 4

After receiving your watch, you can, if
necessary, finely adjust the length of
the strap by moving the pin through the
clasp's holes.

RUBBER STRAP ADJUSTMENT INSTRUCTIONS



STEP 1

Open the clasp.



STEP 2

Push the pin out using a paper clip...




STEP 3

...and remove the bracelet.



STEP 4

Remove the pin.



STEP 5

Following the notches, cut the rubber strap using scissors (or a cutter). When possible, make sure the two parts of the rubber strap are cut so that the clasp and the watch head remain centered once the bracelet is closed.



STEP 6

Insert the pin.



STEP 7

Fix the bracelet.



STEP 8

If necessary, you can finely adjust the length of the strap by moving the pin through the clasp's holes.